AMENDMENT UNDER 37 C.F.R. § 1.116 U.S. Appln. 09/940,474 ATTORNEY DOCKET NO. Q65911

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (currently amended): A separator for non-aqueous electrolyte secondary battery, wherein the separator comprises a shut-down layer, a heat-resistant microporous layer, and a spacer having a form of particles, fibers, net or porous film on the surface of the heat-resistant microporous layer,

wherein the heat-resistant microporous layer comprises at least one heat-resistant resin selected from resins having a temperature of deflection under load of 18.6 kg/cm² pf 100° C or more.

- 2. (original): The separator for non-aqueous electrolyte secondary battery according to claim 1, wherein the heat-resistant microporous layer consists of heat-resistant resin.
 - 3. (canceled).
- 4. (previously presented): The separator for non-aqueous electrolyte secondary battery according to claim 1, wherein the spacer is an electrochemically stable organic polymer, or an electrochemically stable organic layer polymer containing an electrochemically stable inorganic compound.
- 5. (original): The separator for non-aqueous electrolyte secondary battery according to claim 1, wherein the spacer has a form of particles and a particle diameter of 3 μ m or less.

2

AMENDMENT UNDER 37 C.F.R. § 1.116 U.S. Appln. 09/940,474 ATTORNEY DOCKET NO. Q65911

- 6. (original): The separator for non-aqueous electrolyte secondary battery according to claim 1, wherein the static friction coefficient between the spacer-disposed separator surface and a stainless steel surface ground by a 1000 grit polishing paper is 0.5 or less.
- 7. (original): The separator for non-aqueous electrolyte secondary battery according to claim 1, wherein the spacer is formed by coating an application liquid containing an electrochemically stable substance on the surface of the heat-resistant microporous layer.
- 8. (original): The separator for non-aqueous electrolyte secondary battery according to claim 6, wherein the application liquid is a suspension.
- 9. (currently amended): The separator for non-aqueous electrolyte secondary battery according to claim 4, wherein the electrochemically stable substance is an organic polymer selected from the group consisting of a polyolefin, a polyolefin copolymer, a fluorine-containing polymer, a polycarbonate, an aromatic polyester, a polyethylene terephthalate and a cellulose.
- 10. (previously presented): A non-aqueous electrolyte secondary battery including the separator for non-aqueous electrolyte battery according to any one of claims 1 to 8.
- 11. (original): The non-aqueous electrolyte secondary according to claim 10, wherein the spacer is adjacent to a cathode.